

→ Ordering Information

Model Number	Watt	Input Voltage	Form Type	Size	CCT	Lens	AC Hard Cable
LML	36	UM	L	4	D	F	W6
Linear Multi-purpose Luminaire	36 : 36W 45 : 45W	UM : 120-277V	Linear Type	4: 4ft	Y : 3500K N : 4000K D : 5000K	F : Frosted	Blank W6 : 6' AC Hard Cable

→ Specification

Model Number	Power Consumption (W)	Luminous Flux (lm)	Luminaire Efficacy (lm/W)	Input Voltage (Vac)	Color Temperature (K)	CRI (Ra)	Operating Temperature (°F / °C)	Distribution (°)	Dimension (LxWxH)	Weight (lb/kg)	Lifetime (h)
LML36-UM-L4-DF-W6	36	4,500	125	AC 100-277V	5000	80	-4°F to +122°F (-20°C to +50°C)	130 x105°	2.7"x 48"x2.9"	6.6 / 3	50,000
LML36-UM-L4-NF-W6		4,320	120		4000						
LML36-UM-L4-YF-W6		4,150	115		3500						
LML36-UM-L4-DF		4,500	125		5000					6.2 / 2.8	
LML36-UM-L4-NF		4,320	120		4000						
LML36-UM-L4-YF		4,150	115		3500						
LML45-UM-L4-DF-W6	45	5,900	131	AC 100-277V	5000	80	-4°F to +113°F (-20°C to +45°C)	130 x105°	2.7"x 48"x2.9"	6.6 / 3	50,000
LML45-UM-L4-NF-W6		5,670	126		4000						
LML45-UM-L4-YF-W6		5,440	121		3500						
LML45-UM-L4-DF		5,900	131		5000					6.2 / 2.8	
LML45-UM-L4-NF		5,670	126		4000						
LML45-UM-L4-YF		5,440	121		3500						

*Dimension with Side Cover Option is 2.9" x 48.1" x 3.1" [73x1,222x78mm]

> To improve quality, changes and updates in specification may be made without prior notice