

LED 내압 방폭등
Ex d IIC T6 Ex tD A21 T100°C IP66



LUMIDAS EXPLOSION PROOF

EXD Series 29 / 43 / 57 / 80 / 100W



제품 사양 Product specification

○ 5700K

소비전력 (W)	모델명	총광속 (lm)	광효율 (lm/W)	빔각도 (°)	입력전압 (V)	색온도 (K)	연색지수 (Ra)	IP등급	무게 (kg)
29	Ⓐ EXD29-JE-CC	4,437	153	115	AC 100 ~240	5700	80	66	7.0
	Ⓑ EXD29-JE-CP								7.9
	Ⓒ EXD29-JE-CR								6.3
	Ⓓ EXD29-JE-CF								9.1
	Ⓔ EXD29-JE-CJ								10.0
43	Ⓐ EXD43-JE-CC	6,450	150	115	AC 100 ~240	5700	80	66	8.4
	Ⓑ EXD43-JE-CP								9.1
	Ⓒ EXD43-JE-CR								10.0
	Ⓓ EXD43-JE-CF								8.4
	Ⓔ EXD43-JE-CJ								9.1
57	Ⓐ EXD57-JE-CC	8,550	150	115	AC 100 ~240	5700	80	66	8.4
	Ⓑ EXD57-JE-CP								9.1
	Ⓒ EXD57-JE-CR								10.0
	Ⓓ EXD57-JE-CF								8.4
	Ⓔ EXD57-JE-CJ								9.1

Ⓐ 직부 타입 Ⓑ 펜던트 타입 Ⓒ 벽부형 90도 타입 Ⓓ 벽부형 45도 타입 Ⓔ 정션박스 타입



LumiDas Explosion Proof

LED 내압방폭등

소비전력 (W)	모델명	총광속 (lm)	광효율 (lm/W)	빔각도 (°)	입력전압 (V)	색온도 (K)	연색지수 (Ra)	IP등급	무게 (kg)
80	Ⓐ EXD80-JE-CC	12,000	150	115	AC 100 ~240	5700	80	65	9.1
	Ⓑ EXD80-JE-CP								10.0
	Ⓒ EXD80-JE-CR								8.4
	Ⓓ EXD80-JE-CF								9.1
	Ⓔ EXD80-JE-CJ								10.0
100	Ⓐ EXD100-JE-CC	16,000	160	115	AC 100 ~240	5700	80	65	8.4
	Ⓑ EXD100-JE-CP								9.1
	Ⓒ EXD100-JE-CR								10.0
	Ⓓ EXD100-JE-CF								8.4
	Ⓔ EXD100-JE-CJ								9.1

I 등급 : Ex d IIC T6 / Ex tD A21 T100°C IP66



제품 라인업 Ordering Number

구분	소비전력	타입				
		직부 타입 Ceiling	벽부형 90도 타입 Wall 90°	벽부형 45도 타입 Wall 45°	펜던트 타입 Pendant	정션박스 타입 Junction Box
내압 방폭등	29W	EXD29-JE-CC	EXD29-JE-CR	EXD29-JE-CF	EXD29-JE-CP	EXD29-JE-CJ
	43W	EXD43-JE-CC	EXD43-JE-CR	EXD43-JE-CF	EXD43-JE-CP	EXD43-JE-CJ
	57W	EXD57-JE-CC	EXD57-JE-CR	EXD57-JE-CF	EXD57-JE-CP	EXD57-JE-CJ
	80W	EXD80-JE-CC	EXD80-JE-CR	EXD80-JE-CF	EXD80-JE-CP	EXD80-JE-CJ
	100W	EXD100-JE-CC	EXD100-JE-CR	EXD100-JE-CF	EXD100-JE-CP	EXD100-JE-CJ