



→ Specification

Model Number	Wattage (W)	Luminous Flux (lm)	Luminaire Efficacy (lm/W)	Input Voltage (V)	Color Temperature (K)	Operating Temperature (°F / °C)	CRI (Ra)	Distribution (°)	Dimension (LxWxH)	Weight (lb/kg)
SCLH80-UM (CH)-12-WD	80	11,200	140	UM : 120-277 CH : 347-480	3000	UM : -40°F to +113°F (-40°C to +45°C)	80	110	27.5" x 11-3/8" x 1/2"	8.2 / 3.7
SCLH80-UM (CH)-12-YD		11,200	140		3500					
SCLH80-UM (CH)-12-ND		11,600	145		4000					
SCLH80-UM (CH)-12-DD		12,000	150		5000					
SCLH120-UM (CH)-18-WD	120	16,800	140		3000					
SCLH120-UM (CH)-18-YD		16,800	140		3500					
SCLH120-UM (CH)-18-ND		17,400	145		4000					
SCLH120-UM (CH)-18-DD		18,000	150		5000					
SCLH160-UM (CH)-24-WD	160	22,400	140		3000					
SCLH160-UM (CH)-24-YD		22,400	140		3500					
SCLH160-UM (CH)-24-ND		23,200	145		4000					
SCLH160-UM (CH)-24-DD		24,000	150		5000					
SCLH200-UM (CH)-30-WD	200	28,000	140		3000					
SCLH200-UM (CH)-30-YD		28,000	140		3500					
SCLH200-UM (CH)-30-ND		29,000	145		4000					
SCLH200-UM (CH)-30-DD		30,000	150		5000					
SCLH240-UM (CH)-36-WD	240	33,600	140	3000						
SCLH240-UM (CH)-36-YD		33,600	140	3500						
SCLH240-UM (CH)-36-ND		34,800	145	4000						
SCLH240-UM (CH)-36-DD		36,000	150	5000						
SCLH320-UM (CH)-48-WD	320	44,800	140	3000						
SCLH320-UM (CH)-48-YD		44,800	140	3500						
SCLH320-UM (CH)-48-ND		46,400	145	4000						
SCLH320-UM (CH)-48-DD		48,000	150	5000						
						UM : -40°F to +122°F (-40°C to +50°C)			27.6" x 19.3" x 2-3/8"	10 / 4.5

> To improve quality, changes and updates in specification may be made without prior notice

→ Accessories



→ Specification

Model Number	Power Consumption (W)	Luminous Flux (lm)	Luminaire Efficacy (lm/W)	Input Voltage (Vac, Hz)	Color Temperature (K)	CRI (Ra)	Operating Temperature (°F/°C)	Distribution (°)	Dimension (LxWxH)	Weight (lb/kg)	Lifetime (h)
SLH100-UM-12-YD	100	10,500	105	120-277V, 50/60	3500	80	-13°F to +104°F (-25°C to +40°C)	110 / *110 x 60	46.1" x 13" x 2.07"	13 / 5.9	50,000
SLH100-UM-12-ND		11,500	115		4000						
SLH100-UM-12-DD		12,000	120		5000						
SLH200-UM-22-YD	200	20,000	100		3500						
SLH200-UM-22-ND		21,200	106		4000						
SLH200-UM-22-DD		22,000	110		5000						
SLH200-UM-24-YD		23,500	117.5		3500						
SLH200-UM-24-ND		24,000	120		4000						
SLH200-UM-24-DD		24,000	120		5000						
SLH100-CH-12-YD	100	10,500	105	347-480V, 50/60	3500	80	-13°F to +104°F (-25°C to +40°C)	110 / *110 x 60	46.1" x 13" x 2.07"	13 / 5.9	50,000
SLH100-CH-12-ND		11,500	115		4000						
SLH100-CH-12-DD		12,000	120		5000						
SLH200-CH-22-YD	200	20,000	100		3500						
SLH200-CH-22-ND		21,200	106		4000						
SLH200-CH-22-DD		22,000	110		5000						
SLH200-CH-24-YD		23,500	117.5		3500						
SLH200-CH-24-ND		24,000	120		4000						
SLH200-CH-24-DD		24,000	120		5000						

*Distribution for aisle with reflector / Reflector : accessory

> To improve quality, changes and updates in specification may be made without prior notice
> Not recommended to use this luminaire with lens under heavy dust environment

→ Accessories




Pendant Mount



Rod Pendant Mount



Chain Hanger Mount



Reflector



Clear Lens



Frosted Lens



Wire Guard